

Tuscan Texture



The decorative concrete coating that provides the elegance of European style at a fraction of the cost

DESCRIPTION

Sundek's Tuscan texture effect provides the old world European elegance you desire with an investment you can live afford.

This is achieved by hand-trowelling every installation into a custom masterpiece. This eliminates the need for a thicker application of product to be added for the purpose of creating the deeper texture and design elements.

Sundek Design effects such as Custom Scoreline, flagstone, slate and Masonry Effects can be added to further enhance a projects appeal.

Sundek coloring techniques: SunColor, SunGlaze or SunStain are applied to the surface to bring your project to life.



Sundek Products Needed

- **Sundek Additive.**
- **Sundek Premix**
- **Sundek Finish Coat**
- **SunH2O**
- **Sundek Clear (optional)**

Product Description

Sundek Additive – A low solids acrylic binding polymer.

Sundek Premix – An acrylic base cement with medium grade sand.

SunH2O – A water base acrylic stain

Sundek Clear – An acrylic water base sealer (20% solids)

Application Instructions

Clean and etch concrete with a floor machine. Surface may also be diamond ground followed by pressure washing. Squeegee excess water and allow drying until there are no visible signs of water. Slab and ambient temperature above 40 ° and rising, staying above at least 4 hours. Apply a primer if needed. Perform all necessary repairs and install Sundek base coat; a second coat may be applied if required by substrate conditions. Detail and sand to smooth out base coat surface, then apply Sundek Tuscan Texture to area. Detail and lightly sand surface to remove any burrs or imperfections preparing it for SunH2O application. After SunH2O is completely dry, proceed to apply Sundek clear coat for extra protection.