

## SunSplash



*The Economical,  
Textured  
Concrete  
Coating Solution*

### DESCRIPTION

SunSplash is the economical decorative spray textured coating applied to existing vertical or horizontal walking surfaces.

SunSplash provides protection against weather, salts and environmental pollutants resulting in a maintenance friendly coating solution.

SUNDEK Effects such as Custom Scoreline, Aggregate Effects and Masonry Effects can be added to further enhance a projects appeal. Its texture and acrylic properties provide a skid resistant surface ideal for high-traffic areas.



### **Sundek Products Needed**

- **Sundek Undercoat (optional)**
- **Sundek Additive**
- **Sundek Premix**
- **Sundek Finish Coat**
- **Sundek Clear ( optional )**

### **Product Description**

**Sundek Undercoat** – A low solids water base cross linking epoxy.

**Sundek Additive** - A low solids acrylic binding polymer.

**Sundek Premix** - An acrylic base cement with medium grade sand.

**Sundek Finish Coat** – An acrylic water base low solids color dispersion.

**Sundek Clear** – An acrylic water base sealer (20% solids)

### **Application Instructions**

Clean and etch concrete with a floor machine. Surface may also be diamond ground followed by pressure washing. Squeegee excess water and allow drying until there are no visible signs of water. Slab and ambient temperature above 40° and rising staying above at least 4 hours. Apply a primer if needed. Perform all necessary repairs and apply a base coat. Spray SunSplash through out surface. After surface dries, vacuum or blow any loose sand from surface, then proceed to Finish Coat application. Spray Finish coat through out entire surface. After the finish coat is completely dry. If requested, apply Sundek clear coat for extra protection.